

SLR-S



Luce di segnalazione a led (modulo M-LINE).

Led warning beacon (M-LINE range).

Feu de signalisation à LED (module M-LINE)

CUPOLA <i>DOME</i> <i>DOME</i>	PC																										
BASE <i>BASE</i> <i>BASE</i>	PC																										
LENTE <i>LENS</i> <i>LENTILLE</i>	PC																										
GRUPPO OTTICO <i>LUMINOUS SOURCE</i> <i>SOURCE LUMINEUSE</i>	N°2 LED																										
COLORI DISPONIBILI <i>AVAILABLE COLOURS</i> <i>COULEURS DISPONIBLES</i>																											
VOLTAGGIO <i>VOLTAGE</i> <i>TENSION</i>	12/24 Vdc/Vac – 40/80 Vdc/Vac – 120/240 Vac																										
SERVIZIO <i>OPERATION</i> <i>FONCTIONNEMENT</i>	∞																										
CORRENTE NOMINALE <i>CURRENT CONSUMPTION</i> <i>CONSOMMATION DE COURANT</i>	<table border="1"> <tr> <td>LT</td> <td>12 Vdc</td> <td>24 Vdc</td> <td>12 Vac</td> <td>24 Vac</td> </tr> <tr> <td>mA</td> <td>105</td> <td>75</td> <td>230</td> <td>170</td> </tr> </table> <table border="1"> <tr> <td>MT</td> <td>40 Vdc</td> <td>80 Vdc</td> <td>40 Vac</td> <td>80 Vac</td> </tr> <tr> <td>mA</td> <td>135</td> <td>70</td> <td>175</td> <td>110</td> </tr> </table> <table border="1"> <tr> <td>HT</td> <td>120 Vac</td> <td>240 Vac</td> </tr> <tr> <td>mA</td> <td>65</td> <td>45</td> </tr> </table>	LT	12 Vdc	24 Vdc	12 Vac	24 Vac	mA	105	75	230	170	MT	40 Vdc	80 Vdc	40 Vac	80 Vac	mA	135	70	175	110	HT	120 Vac	240 Vac	mA	65	45
LT	12 Vdc	24 Vdc	12 Vac	24 Vac																							
mA	105	75	230	170																							
MT	40 Vdc	80 Vdc	40 Vac	80 Vac																							
mA	135	70	175	110																							
HT	120 Vac	240 Vac																									
mA	65	45																									
RESA LUMINOSA <i>LIGHT OUTPUT</i> <i>RENDEMENT LUMINEUX</i>	<table border="1"> <tr> <td rowspan="2">Cd(p)</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>300</td> <td>100</td> <td>65</td> <td>80</td> <td>60</td> </tr> </table>	Cd(p)						300	100	65	80	60															
Cd(p)																											
	300	100	65	80	60																						
MODALITA' LUCE <i>LIGHT EFFECT</i> <i>EFFET LUMINEUX</i>	1F / 5F / RANDOM / 1F																										
FLASH/MIN <i>FLASHES PER MINUTE</i> <i>ECLATS PAR MINUTE</i>	1F x 120 ± 10 - 5F x 40 ± 10 - Random - 1F x 85 ± 10																										
GRADO IP <i>IP RATING</i> <i>DEGRE IP</i>	IP66 (69K: con collare di sicurezza/guaranteed with safety collar/garanti avec le collier de sûreté)																										

Dati diffusi a solo scopo informativo. Sirena S.p.A. puo' modificare i dati in qualsiasi momento senza preavviso.
 These data are disclosed only for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.
 Les données ne sont divulguées qu'à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis

GRADO IK IK RATING DEGRE IK	IK07 (utilizzo del collare di sicurezza) (use of the safety collar) (emploi du collier de sûreté)
TEMPERATURA DI FUNZIONAMENTO OPERATING TEMPERATURE TEMPERATURE DE SERVICE	-40°C+55°C
VIBRAZIONI VIBRATIONS VIBRATIONS	INDUSTRIAL CEI 60068-2-6 SINE
CERTIFICAZIONI, OMOLOGAZIONI CERTIFICATIONS, APPROVALS CERTIFICATIONS, HOMOLOGATIONS	CE, UL, EAC
FISSAGGIO MOUNTING FIXATION	MODULARE Modular Modulaire
DISEGNO TECHNICAL DRAWING DESSIN	