

## XLF RGB



Luce di segnalazione a led multicolore.  
 Multi-coloured led signal light.  
 Feu de signalisation à LED multicolore

<b>CUPOLA</b> DOME DOME	Directional = PC Proximity = PC Opaline																														
<b>GRUPPO OTTICO</b> LUMINOUS SOURCE SOURCE LUMINEUSE	N°1 LED RGBA																														
<b>COLORI DISPONIBILI</b> AVAILABLE COLOURS COULEURS DISPONIBLES																															
<b>VOLTAGGIO</b> VOLTAGE TENSION	12÷24 Vdc/Vac - 40÷80 Vdc/Vac - 90÷240 Vac																														
<b>SERVIZIO</b> OPERATION FONCTIONNEMENT	∞																														
<b>CORRENTE NOMINALE</b> CURRENT CONSUMPTION CONSOMMATION DE COURANT	<table border="1"> <tr> <td>LT</td> <td><b>12 Vdc</b></td> <td><b>24 Vdc</b></td> <td><b>12 Vac</b></td> <td><b>24 Vac</b></td> </tr> <tr> <td>mA</td> <td>250</td> <td>155</td> <td>250</td> <td>155</td> </tr> </table> <table border="1"> <tr> <td>MT</td> <td><b>40 Vdc</b></td> <td><b>80 Vdc</b></td> <td><b>40 Vac</b></td> <td><b>80 Vac</b></td> </tr> <tr> <td>mA</td> <td>145</td> <td>80</td> <td>230</td> <td>135</td> </tr> </table> <table border="1"> <tr> <td>HT</td> <td><b>120 Vac</b></td> <td><b>240 Vac</b></td> </tr> <tr> <td>mA</td> <td>100</td> <td>75</td> </tr> </table>	LT	<b>12 Vdc</b>	<b>24 Vdc</b>	<b>12 Vac</b>	<b>24 Vac</b>	mA	250	155	250	155	MT	<b>40 Vdc</b>	<b>80 Vdc</b>	<b>40 Vac</b>	<b>80 Vac</b>	mA	145	80	230	135	HT	<b>120 Vac</b>	<b>240 Vac</b>	mA	100	75				
LT	<b>12 Vdc</b>	<b>24 Vdc</b>	<b>12 Vac</b>	<b>24 Vac</b>																											
mA	250	155	250	155																											
MT	<b>40 Vdc</b>	<b>80 Vdc</b>	<b>40 Vac</b>	<b>80 Vac</b>																											
mA	145	80	230	135																											
HT	<b>120 Vac</b>	<b>240 Vac</b>																													
mA	100	75																													
<b>RESA LUMINOSA</b> LIGHT OUTPUT RENDEMENT LUMINEUX	<table border="1"> <thead> <tr> <th></th> <th>DIRECTIONAL</th> <th>PROXIMITY</th> </tr> </thead> <tbody> <tr> <td>Cd(p)</td> <td>165</td> <td>11</td> </tr> <tr> <td></td> <td>145</td> <td>10</td> </tr> <tr> <td></td> <td>135</td> <td>9</td> </tr> <tr> <td></td> <td>40</td> <td>4</td> </tr> <tr> <td></td> <td>125</td> <td>7</td> </tr> <tr> <td></td> <td>100</td> <td>6</td> </tr> <tr> <td></td> <td>55</td> <td>5</td> </tr> <tr> <td></td> <td>25</td> <td>2</td> </tr> <tr> <td>Angolo del Fascio Luminoso</td> <td>60 Gradi</td> <td></td> </tr> </tbody> </table>		DIRECTIONAL	PROXIMITY	Cd(p)	165	11		145	10		135	9		40	4		125	7		100	6		55	5		25	2	Angolo del Fascio Luminoso	60 Gradi	
	DIRECTIONAL	PROXIMITY																													
Cd(p)	165	11																													
	145	10																													
	135	9																													
	40	4																													
	125	7																													
	100	6																													
	55	5																													
	25	2																													
Angolo del Fascio Luminoso	60 Gradi																														
<b>MODALITA' LUCE</b> LIGHT EFFECT EFFET LUMINEUX	Fissa / 1F / 3F / 5F / Random Steady/Flashing Fixe/Clignotant																														
<b>FLASH/MIN</b> FLASHES PER MINUTE ECLATS PAR MINUTE	1F X 120 ± 10, 3F X 40 ± 10, 5F X 40 ± 10, Random																														
<b>GRADO IP</b> IP RATING DEGRE IP	IP66																														

**Dati diffusi a solo scopo informativo. Sirena S.p.A. puo' modificare i dati in qualsiasi momento senza preavviso.**  
 These data are disclosed only for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.  
 Les données ne sont divulguées qu'à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis

<b>GRADO IK</b> <i>IK RATING DEGRE IK</i>	IK08 (utilizzo del collare di sicurezza) <i>(use of the safety collar) (emploi du collier de sûreté)</i>
<b>TEMPERATURA DI FUNZIONAMENTO</b> <i>OPERATING TEMPERATURE TEMPERATURE DE SERVICE</i>	-40°C+55°C
<b>VIBRAZIONI</b> <i>VIBRATIONS VIBRATIONS</i>	INDUSTRIAL CEI 60068-2-6 SINE
<b>CERTIFICAZIONI, OMOLOGAZIONI</b> <i>CERTIFICATIONS, APPROVALS CERTIFICATIONS, HOMOLOGATIONS</i>	CE, UL, EAC
<b>FISSAGGIO</b> <i>MOUNTING FIXATION</i>	Mediante basi modulari <i>Using the modular bases Moyennant les bases modulaires</i>
<b>DISEGNO</b> <i>TECHNICAL DRAWING DESSIN</i>	